ID:

OPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Burcau



ATTEN (ALL DELINIO LORI DELINIO LORI DELINIO ALBON ALBON ALLO ALLO ALBON ALBON ALBON ALBON ALBON ALBON ALBON A

(43) International Publication Date 17 August 2000 (17.08.2000)

PCT

(10) International Publication Number WO 00/47927 A3

- (51) International Patent Classification?: E
 - B21D 41/04,
- (21) International Application Number: PCT/GB00/00430
- (22) International Filing Date: 11 February 2000 (11.02.2000)
- (25) Filing Language:

English

(26) Publication Language:

English

- (30) Priority Data:
 - 9903150.2

12 February 1999 (12.02.1999) GI

- (71) Applicants (for all designated States except US):
 SCHOOLHILL HYDRAULIC ENGINEERING
 COMPANY LIMITED [GB/GB]; 4 Greenbank Place,
 East Tullos, Aberdoen AB12 3RJ (GB). MAXTUBE
 LIMITED [GB/GB]; Hareness Road, Altens, Aberdoen
 AB12 3LE (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): WHYTE, Ronald [GB/GB]; 2 West Cults Road, Cults. Aberdeen AB15

9HN (GB). MUDGE, Joseph, Krist [US/GB]; 22 Cults Avenue, Aberdeen AB15 9RS (GB). McLAUCHLIN, Thomas, Kilpatrick [GB/GB]: 3 Keir Rise, Balmedic, Aberdeenshire AB23 8TW (GB).


- (74) Agent: MURGITROYD & COMPANY; 373 Scotland Street, Glasgow G5 8QA (GB).
- (81) Designated Stokes (national): AE, AL, AM, AI, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SL, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW). Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

With insernational search report.

[Continued on next page]

(54) Title: APPARATUS FOR SWAGING AN OBJECT



(57) Abstract: An apparatus for swaging an end of a tubular (22) is described as comprising a swaging head (17) for providing the swage to the end of the tubular (22). The swaging head (17) has two or more swaging formations (22A, 22B) provided thereon to permit swaging of differing diameters of tubular ends. The apparatus may comprise a stop plate (5, 9) for abuttment against the other end of the tubular (22), where the swaging head (17) and the stop plate (5, 9) are movably coupled to one another. The apparatus may have a clamping device (4) for clamping the tubular (22), where the clamping device is split into at least three part-circular clamping segments (30) which clamp around the outer circumference of the tubular to permit it to be swaged. The clamping device (4) may have a plurality of teeth (35) for gripping the outer surface of the tubular (22), and a plurality of grooves (36) formed between the teeth (35). The gripping surface of each tooth (35) is substantially parallel to the longitudinal axis of the tubular (2) to be gripped.

BEST AVAILABLE COPY

WO 00/47927 A3



(88) Date of publication of the international search report: 5 April 2001

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

That feet man